FILE LAYOUT IRPXML V 1.0

IMPORT RETURNED PAYMENT SLIPS
2019-08-05

VERSIONS

Version	Date	Description of change	Changed by
1.0	2019-08-05	First version	Seva Posviatenko

CONTENTS

1. INTRODUCTION

File layout IRPXML, import returned payment slips, is used to import information about payment returns into all ARC's modules. The import file is an XML-file that must follow a specific scheme.

XML-scheme can be found at http://schema.aptic.net/aptic-link-import-returnedpayments.xsd.
In the scheme, all fields that are available can be interpreted; we can determine the order of these and even point out which ones are required to be filled in. Many fields are optional and some of those fields might be replaced with default values if empty.

2. EXAMPLE

The example below shows an XML file having payment returns in it. There are three payment references to be returned after the success import: PMTREF666444648, PMTREF167064678 and PMTREF674350842.

```xml
<?xml version="1.0" encoding="utf-8"?>
<returnedpayments xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:noNamespaceSchemaLocation="http://schema.aptic.net/aptic-link-import-
returnedpayments.xsd">
  <returnedpayment>
    <intransitreference>PMTREF666444648</intransitreference>
  </returnedpayment>
  <returnedpayment>
    <intransitreference>PMTREF167064678</intransitreference>
  </returnedpayment>
  <returnedpayment>
    <intransitreference>PMTREF674350842</intransitreference>
  </returnedpayment>
</returnedpayments>
```

3. ELEMENT DESCRIPTIONS

Below you can find a short element description of the elements that are available.

Element	Type	Required	Description
returnedpayments / returnedpayment			
@intransitreference	String(64)	Required	Returned payment reference.